Certificate Number UL-CA-L503749-92409102-2

Report Reference E503749-20190429

Date 2-Mar-2023

Issued to: SHINENERGY TECHNOLOGY (SHANGHAI) LTD

BLDG 5, LINGGANG INDUSTRIAL PARK

NO 239 NORTH HONGXIANG RD

WANXIANG PUDONG, SHANGHAI 201313

China

This is to certify that representative samples of

XQNX8 - Power and General-purpose Transformers, Dry

Type Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 47-13, 5th Ed., Issue Date: 2013-09-01,

Reaffirmed 2018

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Debrah Lennings-Course

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/



Certificate Number UL-CA-L503749-92409102-2

Report Reference E503749-20190429

Date 2-Mar-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
MPT-XX-XXX-WZY-NNN Series (a), (a) Factory ID	Dry type distribution component
(b) K factor	transformer
01 = K1	
02 = K2	
03 = K3	
04 = K4	
(c) Size (KVA rating)	
225 = 225 KVA, 250 = 250 KVA, 275 = 275 KVA	
300 = 300 KVA, 315 = 315 kVA, 325 = 325 kVA, 360 =	
360 kVA , 375 = 375 kVA	
400 = 400 kVA, 425 = 425 kVA, 450 = 450 kVA, 475 =	
475 kVA	
450 = 450 kVA	
500 = 500 kVA, 525 = 525 kVA, 550 = 550 kVA, 575 =	
575 kVA	
600 = 600 kVA, 630 = 630 kVA, 650 = 650 kVA, 675 =	
675 kVA	
700 = 700 kVA, 725 = 725 kVA, 750 = 750 kVA, 775 =	
775 kVA	
800 = 800 kVA, 825 = 825 kVA, 850 = 850 kVA, 875 =	
875 kVA	
900 = 900 kVA, 925 = 925 kVA, 950 = 950 kVA	
(d) Primary voltage (See Voltage Code)	
(e) Secondary voltage (See Voltage Code)	
(f) Material of windings	
A = Copper	
B = Aluminium	
(g) NNN – Non-Safety Critical Suffix, assigned by	
manufacturer, 000 to 999	

Olbrah Jennings-Course

Deborah Jennings-Conner, VP Regulatory Services





Certificate Number UL-US-L503749-92409102-2

Report Reference E503749-20190429

Date 2-Mar-2023

Issued to: SHINENERGY TECHNOLOGY (SHANGHAI) LTD

BLDG 5, LINGGANG INDUSTRIAL PARK

NO 239 NORTH HONGXIANG RD

WANXIANG PUDONG, SHANGHAI 201313

China

This is to certify that representative samples of

XQNX2 - Power and General-purpose Transformers, Dry

Type - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1561, 4th Ed., Issue Date: 2011-03-02, Revision Date:

2019-05-13

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Gebrah Jennings-Course

(UL)

Certificate Number UL-US-L503749-92409102-2

Report Reference E503749-20190429

Date 2-Mar-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
MPT-XX-XXX-WZY-NNN Series (a), (a) Factory ID	Dry type distribution component
(b) K factor	transformer
01 = K1	
02 = K2	
03 = K3	
04 = K4	
(c) Size (KVA rating)	
225 = 225 KVA, 250 = 250 KVA, 275 = 275 KVA	
300 = 300 KVA, 315 = 315 kVA, 325 = 325 kVA, 360 =	
360 kVA , 375 = 375 kVA	
400 = 400 kVA, 425 = 425 kVA, 450 = 450 kVA, 475 =	
475 kVA	
450 = 450 kVA	
500 = 500 kVA, 525 = 525 kVA, 550 = 550 kVA, 575 =	
575 kVA	
600 = 600 kVA, 630 = 630 kVA, 650 = 650 kVA, 675 =	
675 kVA	
700 = 700 kVA, 725 = 725 kVA, 750 = 750 kVA, 775 =	
775 kVA	
800 = 800 kVA, 825 = 825 kVA, 850 = 850 kVA, 875 =	
875 kVA	
900 = 900 kVA, 925 = 925 kVA, 950 = 950 kVA	
(d) Primary voltage (See Voltage Code)	
(e) Secondary voltage (See Voltage Code)	
(f) Material of windings	
A = Copper	
B = Aluminium	
(g) NNN – Non-Safety Critical Suffix, assigned by	
manufacturer, 000 to 999	

Octoah Jennings-Corne

Deborah Jennings-Conner, VP Regulatory Services



